# SAFETY DATA SHEET

Issued : 2010-11-24 Revised : 2015-12-03 SDS No. : EG-S314-2

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product identity

·Product name: Liquid acrylic resin

•Product number: S-314

Supplier's details

Manufacturer: CHEMITECH INC.Department issuing SDS: Quality-related Gr.

·Address: 4-9-1, Shinmeidai, Hamura-shi, Tokyo, 205-0023, JAPAN

• TEL No. : +81-(0) 42-553-6100• FAX No. : +81-(0) 42-553-6108• Emergency phone No. Same as above

Recommended use of the chemical and restriction on use:

UV-ray curing resin (for industrial use)

#### 2. HAZARDS IDENTIFICATION

\*GHS classification

Physical hazards

Explosives:
 Not applicable
 Flammable gases:
 Not applicable
 Oxidizing gases:
 Gases under pressure:
 Flammable liquids:
 Flammable solids:
 Not applicable
 Category 4
 Flammable solids:
 Not applicable

•Self-reactive substances and mixtures:

Classification not possible

Pyrophoric liquids: Not applicablePyrophoric solids: Not applicable

·Self-heating substances and mixtures:

Classification not possible

·Substances and mixtures which, in contact with water, emit flammable gases:

Not applicable

•Oxidizing liquids:Not applicable•Oxidizing solids:Not applicable•Organic peroxides:Not applicable

·Corrosive to metals: Classification not possible

Health hazards

·Acute toxicity / Oral: Category 4 ·Acute toxicity / Skin: Category 3

·Acute toxicity / Inhalation

- gases: Not applicable

- vapor: Classification not possible

- dust or mist: Classification not possible

·Skin corrosion / irritation: Category 1A

•Serious eye damage / eye irritation:

Category 1

•Respiratory sensitization: Classification not possible

·Skin sensitization: Category 1

•Germ cell mutagenicity: Classification not possible ·Carcinogenicity: Classification not possible ·Toxic to reproduction: Classification not possible

Specific target organ systemic toxicity

- Single exposure: Classification not possible - Repeated exposure: Category 1 (respiratory system) •Aspiration hazard: Classification not possible

Environmental hazards

·Hazardous to the aquatic environment

Category 3 - Acute:

- Chronic: Classification not possible

Symbols:







Signal words: Danger

Hazard statement: Combustible liquid

Harmful if swallowed (oral)

Toxic in contact with skin (dermal)

Causes severe skin burns and eye damage

· May cause an allergic skin reaction

 Causes damage to organ (respiratory system) through prolonged or repeated exposure

Harmful to aquatic life

Precautionary statement

•Prevention: Wear protective gloves / protective cloth /

eye protection / face protection.

Avoid release to the environment.

• Do not eat, drink or smoke when using this product.

• Wash (hands, face and body) carefully after handling.

• Contaminated work clothing should not be allowed out

of the workplace.

Keep away from open flames / hot surfaces.

• Do not breathe dust / vapor / mist / spray.

Avoid breathing dust / vapor / mist / spray.

Rinse mouth.

[If inhaled] • Remove person to fresh air and keep comfortable for

breathing.

Call a doctor / physician if you feel unwell.

Get medical advice / attention if you feel unwell.

· Wash contaminated clothing before reuse.

[If on skin (or hair)] • Take off immediately all contaminated clothing.

Rinse skin with water / shower.

·Response:

[If on skin] • Wash with plenty of soap and water.

 Get medical advice / attention if skin irritation or rash occurs.

Take off immediately all contaminated clothing.

Immediately call a doctor / physician.

[If in eyes] • Flush eyes immediately with plenty of water for

several minutes. Remove contact lenses, if worn, after initial flushing, and continue flushing.

[If swallowed] • Rinse mouth. Do not induce vomiting. Call a doctor

/ physician if you feel unwell.

Storage: Store locked up.

Store in a well ventilated place. Keep cool.

·Disposal: • Dispose of contents / container to in accordance with

local / regional / national / international regulation. Ask a qualified trader with approved qualification for

trading.

•Others • According to the results investigated by the MHLW,

the mutagenicity of 2-Hydroxyethyl acrylate has been

recognized. (in Japan)

# 3. COMPOSITION, INFORMATION ON INGREDIENTS

Single or mixture: Mixture

Chemical name: Liquid acrylic resin

Synonym: — Chemical characteristics: —

Components:

Components	Contents Wt. %	CAS No.
Acrylate monomer	45 - 55	Secret
Urethane acrylate prepolymer	15 – 25	Secret
2-Hydroxyethyl acrylate	18	818-61-1
Photo-initiating agent	<10	Secret
Additive	<1.0	Secret
Methanol	<10	67-56-1
Amount	100.0	

Hazardous ingredients: 2-Hydroxyethyl acrylate, Methanol

Hazardous impurities: —

# 4. FIRST AID MEASURES

Inhalation: If inhaled, remove to fresh air. Consult a physician

if not recovered.

Touched skin: Wipe off the adhered materials and flush the skin with

water and soap. Consult a physician if inflammation

or itching symptoms shown.

Splashed in eyes: Flush eyes immediately with plenty of water for more

than 15 minutes and consult a physician.

Ingestion: Do not induce vomiting. Give plenty of water to drink

and consult a physician as soon as possible.

The symptoms and effects should be summarized briefly:

Protection for first-aiders: —
Note to physicians: —

#### 5. FIRE FIGHTING MEASURES

Extinguishing media: Air foam, carbon dioxide, dry sand, powder

Unsuitable extinguishing media:

Hazardous gases produced in fire: Organic gases, carbon monoxide

Fire fighting instructions: Use appropriate extinguishing media and put out from

upwind of the fire. Guard against intruders.

Protection for fire fighters: Wear appropriate protective equipment. Make fire

fighting activities from upwind of the fire.

# 6. ACCIDENTAL RELEASE MEASURES

Safeguard (personnel): Put on impermeable protective gloves, and avoid

contact and inhalation. Ventilate the room and make

activities from upwind of the spill.

Precautions for environment:

Prevent materials from entering waterways and sewers.

Removal

Recovery:
 If the spill is small, wipe it off with paper.

• If the spill is large, dike spill and recover it.

·Neutralization:

·Disposal: Observe instructions in Article 13.

Prevention of secondary damage: Remove all source of ignition, stop leakage as soon

as possible.

# 7. HANDLING AND STORAGE

Handling

·Technical measures

- Prevention of exposure: • Use protective means to avoid contact.

Ventilate workroom to avoid inhalation.

Wash hand and face carefully after handling.

- Prevention of fire and explosion:

Keep the material away from all sources of ignition

and items whose temperature is higher than 40°C.

·Precautions: —

·Precautions for safe handling: It is necessary to take countermeasures following

the guidance of the Labor Standard Bureau (2) .

Storage

·Suitable storage conditions

- Suitable storage conditions: Keep the container in a cold and dark place, and

keep off fire or heat sources.

- Unsuitable storage conditions: UV rays, direct sun light, heat up

•Materials to avoid contact: Acid. base, peroxide

·Containers: Keep the material in the supplied container.

(Do not transfer to other containers)

# 8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Facilities: Ventilate the workroom and install exhaust fans on

the UV irradiating or heating equipment.

Control concentration: 200ppm : Methanol

Permissible concentration

·ACGIH-TLV (2005): 200ppm (TWA) : Methanol

Protective means

•For respiratory system: Wear respirator for organic gases as required.
•For hands: Wear protective gloves (disposable type) made of

impermeable materials.

\* Do not use gloves made of permeable materials such

as cotton.

·For eyes: Wear goggles suitable for chemical products.

·For skin and body: Apron (impermeable material) and long-sleeved work

clothes.

Appropriate sanitary measures: —

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical properties

Appearance: LiquidColor: Milky whiteOdor: Acrylic odorpH: No data

Specific temperature (temperature range) at which physical properties have a discontinuity

·Boiling point: No data ·Boiling range: No data ·Melting point: No data ·Decomposition point: No data ≥ 85°C Flash point: Ignition point: No data Explosion characteristic: No data No data Vapor pressure: Vapor density: No data Specific gravity: 1. 1 (25°C)

Solubility

·For solvent: Insoluble (water)

·Octanol / water distribution coefficient:

No data

# 10. STABILITY AND REACTIVITY

Stability: • Stable in sealed container.

Stored in cool and dark place.

Hazardous reaction under special conditions:

Polymerization and heat generation

Conditions not to be exposed: Visible ray, UV rays, direct sun light, heat up,

fire, contact with metals, static electricity

Materials contact to be avoided: Acid, base, peroxide

Hazardous gases produced by decomposition:

Organic gases, carbon monoxide, Carbon dioxide etc

# 11. TOXICOLOGICAL INFORMATION

Acute toxicity: • rat (oral) LD50

> 7, 939mg/kg : Methanol

> 2,400mg/kg : Acrylate monomer

> 2,000mg/kg : Photo-initiating agent > 540mg/kg : 2-Hydroxyethyl acrylate

rabbit (dermal) LD50

> 15, 800mg/kg : Methanol

> 1,100mg/kg : Photo-initiating agent

rat (inhalation) LC50

> 22, 500ppm/L/4h : Methanol

> 1.87mg/L/4h : 2-Hydroxyethyl acrylate

Local effect: Flammables may occur in direct touch for a long time

or in repeated use.

Skin Corrosion / irritation:

Irritation • rabbit

Ext. severe : 2-Hydroxyethyl acrylate

Moderate : Acrylate monomer

Methanol

Negative : Photo-initiating agent

Eye Damage / irritation:

Damage • rabbit

Severe : 2-Hydroxyethyl acrylate

Irritation • rabbit

Moderate : Methanol

Negative : Photo-initiating agent

Respiratory Organs Sensitizing

or Skin Sensitization: • Cavia porcellus (skin)

Positive : 2-Hydroxyethyl acrylate

Germ Cell Mutagenicity (Mutagenicity)

Mutagenicity test, Chromosomal aberration test

Positive : 2-Hydroxyethyl acrylate

\* According to the results investigated by the MHLW, mutagenicity of 2-Hydroxyethyl acrylate has been recognized that exceeds the standards stipulated in tests of the mutagenicity (using microorganism) and the chromosomal mutagenicity (using mammal cells).

This product is suspected of causing health

damages (1).

It is also necessary to take countermeasures following the guidance of the Labor Standard

Bureau(2). (in Japan)

Micronucleus test Negative : Photo-initiating agent

Carcinogenicity: No data
Reproductive tox: No data
Target Organ Systemic Toxicity: No data

(Single exposure)

Target Organ Systemic Toxicity: respiratory system: 2-Hydroxyethyl acrylate

(Repeated exposure)

Aspiration Hazard No data

#### 12. ECOLOGICAL INFORMATION

Ecotoxicity

Fish toxicity
 danio rerio
 LC50 / 96h

> 24mg/L : Photo-initiating agent

• Others: • daphnia magna EC50 / 48h

> 5. 2mg/L : 2-Hydroxyethyl acrylate

Persistency/Bio-degradability: Rapidly degradable : 2-Hydroxyethyl acrylate

Accumulation in organism: No data
Mobility: No data
Harmful effect on the ozone layer:No data

#### 13. DISPOSAL CONSIDERATIONS

Ask a qualified trader with approved qualification for trading the waste to disuse it.

# 14. TRANSPORTATION INFORMATION

International regulations

UN No.: None
Proper Shipping name: None
Hazard Class: None
Packing Grroup: None
Marine Pollutant Material: None
Other regulations: None
Safety precautions for transportation:

Be sure containers have no leakage. Pile the containers in an orderly manner so that no collapse and damage

happens during transportation.

Others: Observe all instructions in Article 7 for transportation.

Materials not to be transported together:

None

# 15. REGURATORY INFORMATION

Please refer to national regulations that may be relevant.

# 16. OTHER INFORMATION

- •This information is furnished without warranty. The figures shown in this document, such as content of each component and physical properties, are not guaranteed value.
- ·No information about harmfulness of the product exists at present.
- This SAFETY DATA SHEET is prepared for the safe handling of the product, based on the currently available information, including those from raw Material manufacturers. So, it might not be sufficient for safety use. Please pay attention in handling.
- •Only ordinary uses are considered to prepare the precautions in this document. If nonordinary use is planned, user should take additional safety measures appropriate to that purpose.
- ·Reference:
- (1) Notification of the Labor Standard Bureau About dealing with the chemicals which

- mutagenicity has been recognized 1994.6.6 No.341-2 issued by the Labor Standard Bureau.
- (2) Notification of the Labor Standard Bureau Guidance for preventing health damages caused by the chemicals which mutagenicity has been recognized. 1993. 5. 17 Appendix to the No. 312-3 issued by the Labor Standard Bureau.
- ·This SDS may be revised when new knowledge is obtained.